

PASSIVE MODULES FOR TELESTE DEVICES

These modules are compatible with Teleste amplifiers and nodes of the AC and CXE series.

EQ862-XX-T EQUALIZER MODULE

GENERAL TECHNICAL SPECIFICATIONS

Frequency range [MHz]	5-862
Return loss [dB]	>18
Temperature range [°C]	-40...+60

ORDERING INFORMATION

E	Q	8	6	2	-	X	X	-	T
---	---	---	---	---	---	---	---	---	---

↓

Tilt value	
5	5 dB
7.5	7.5 dB
10	10 dB
12.5	12.5 dB
15	15 dB



EQXXX-J-T EQUALIZER UNIT TUNABLE BY STANDARD JXP MODULES

GENERAL TECHNICAL SPECIFICATIONS


	EQ302-J-T	EQ862-J-T
Frequency range [MHz]	5-302	5-862
Return loss (return path) [dB]		>18
Temperature range [°C]		-40...+60

ORDERING INFORMATION

E	Q	X	X	X	-	J	-	T
---	---	---	---	---	---	---	---	---

↓

Bandwidth	
302	302 MHz
862	862 MHz



Specifications are subject to change without notice!

J0-T JUMPER MODULE

GENERAL TECHNICAL SPECIFICATIONS

Frequency range [MHz]	5-1218
Return loss (return path) [dB]	>18
Temperature range [°C]	-40...+60

ORDERING INFORMATION

J	0	-	T
---	---	---	---



SP2-T OUTPUT SPLITTER MODULE

GENERAL TECHNICAL SPECIFICATIONS

Frequency range [MHz]	5-1218
Loss [dB]	<4
Return loss (return path) [dB]	>18
Temperature range [°C]	-40...+60

ORDERING INFORMATION

S	P	2	-	T
---	---	---	---	---

